

24" REMOVABLE SHOCK RACKS

When maximum shock absorption is needed with a sliding rack in the smallest exterior dimensions, this is the choice for this depth

Removable shock rack with patented "positive lock" latching system that slides open like a drawer



FEATURES

- Completely removable frame for access to bench integration
- Meets or exceeds MIL-STD-810G
- Standard payload range 40 to 150 lbs
- Optional extended payload range 160 to 300 lbs
- Standard 19" rack width per ANSI/EIA-310-C
- Standard rack depth 24" rail to rail
- Square hole rack rails to accommodate either #10-32 US standard, or 6mm international standard cage nuts - hardware included
- 2" front lid, and 5" rear lid with edge casters (standard); other options available
- SKB's rugged roto-molded shell ensures industry leading strength and impact resistance
- Molded in stacking ribs and lugs are designed to stack with competitive manufacturers' cases
- Black powder coated stainless steel hardware (standard) which is recessed for protection
- 8 comfort grip spring loaded lift handles
- Automatic ambient pressure relief valve (standard)
- Lid hangers (standard)
- Case coupling straps (standard)

AVAILABLE SIZES

Model #	Lid Depth		Rack Units	Rack Height
	Front	Rear		
3RR-3U24-25B	2" 5.1 cm	5" 12.7 cm	3U	5.25" 13.3 cm
3RR-4U24-25B	2" 5.1 cm	5" 12.7 cm	4U	7" 17.8 cm
3RR-5U24-25B	2" 5.1 cm	5" 12.7 cm	5U	8.75" 22.2 cm
3RR-7U24-25B	2" 5.1 cm	5" 12.7 cm	7U	12.25" 31.1 cm
3RR-9U24-25B	2" 5.1 cm	5" 12.7 cm	9U	15.75" 40 cm
3RR-11U24-25B	2" 5.1 cm	5" 12.7 cm	11U	19.25" 48.9 cm
3RR-14U24-25B	2" 5.1 cm	5" 12.7 cm	14U	24.5" 62.2 cm

ACCESSORIES

3SKB-SA Shock Absorber Kit
Set of 8 extra shock absorbers with a capable load range of 40 to 150 lbs (18 kg to 68 kg)



3SKB-SLP Shipping Label Plate
12" x 7" aluminum label (comes with installation kit)



3SKB-SR24 24" Support Rails
Zinc plated steel rails to support additional weight

