

30" STATIC SHOCK RACKS

When maximum shock isolation is needed but a sliding frame is not, this fixed rack case gives our best performance with the smallest exterior dimension foot print for this depth

30" deep static frame shock racks with square hole rails, and the same durability/strength as the 3RR



FEATURES

- Meets or exceeds MIL-STD-810G
- Standard payload range 40 to 150 lbs
- Optional extended payload range 160 to 300 lbs
- Standard 19" rack width per ANSI/EIA-310-C
- Standard rack depth 30" rail to rail
- Square hole rack rails to accommodate either #10-32 US standard, or 6mm international standard cage nuts - hardware included
- 2" front lid, and 5" rear lid with edge casters (standard); other options available
- SKB's rugged roto-molded shell ensures industry leading strength and impact resistance
- Molded in stacking ribs and lugs are designed to stack with competitive manufacturers' cases
- Black powder coated stainless steel hardware (standard) which is recessed for protection
- 8 comfort grip spring loaded lift handles
- Automatic ambient pressure relief valve (standard)
- Lid hangers (standard)
- Case coupling straps (standard)
- Reduced footprint
- Low profile
- Light weight
- Lifetime warranty

AVAILABLE SIZES

Model #	Lid Depth		Rack Units	Rack Height
	Front	Rear		
3RS-3U30-25B	2" 5.1 cm	5" 12.7 cm	3U	5.5" 14 cm
3RS-4U30-25B	2" 5.1 cm	5" 12.7 cm	4U	7" 17.8 cm
3RS-5U30-25B	2" 5.1 cm	5" 12.7 cm	5U	8.75" 22.2 cm

ACCESSORIES

3SKB-SA Shock Absorber Kit
Set of 8 extra shock absorbers with a capable load range of 40 to 150 lbs (18 kg to 68 kg)



3SKB-SLP Shipping Label Plate
12" x 7" aluminum label (comes with installation kit)



3SKB-SR30 30" Support Rails
Zinc plated steel rails to support additional weight

